## AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) An anchor for connecting a building structural member to a cementitious material comprising:

a connection portion designed for connection to the building structural member above the cementitious material; ~~and~~

an embedment portion integrally joined with and coplanar with said connection portion and designed for embedment in said cementitious material, said embedment portion including at least one anchoring leg having an upper end and a lower free end, said at least one anchoring leg having first and second leg sections, said first leg section located closer to said upper end than said second leg section and said second leg section located closer to said free end than said first leg section, said second leg section having a width dimension greater than said first leg section; and

first and second laterally spaced supporting seat members integrally joined with said embedment portion along respective first and second bend lines.

2. (Previously Presented) The anchor of claim 1 including a pair of laterally spaced anchoring legs, each having first and second leg sections, said first leg section located closer to said upper end than said second leg section and said second leg section located closer to said free end than said first leg section, said second leg section having a width dimension greater than said first leg section.

3. (Original) The anchor of claim 2 wherein each of said pair of anchoring legs includes an inner edge and a flange extending from said inner edge.

4. (Original) The anchor of claim 3 wherein each of said pair of anchoring legs includes a foot member at said free end.

5-7. (Cancelled)

7. (Cancelled)

8. (Currently Amended) ~~The~~ An anchor ~~of claim 7 wherein~~ for connecting a building structural member to a cementitious material comprising:

a connection portion designed for connection to the building structural member above the cementitious material; ~~and~~

an embedment portion integrally joined with and coplanar with said connection portion and designed for embedment in said cementitious material, said embedment portion including at least one anchoring leg having an upper end and a lower free end, said at least one anchoring leg having first and second leg sections, said first leg section located closer to said upper end than said second leg section and said second leg section located closer to said free end than said first leg section, said second leg section having a width dimension greater than said first leg section; and

first and second supporting seat members each having a supporting seat for supporting said building structural member and each ~~of said supporting seats includes~~ including an outer, upwardly extending connection flange and a connection opening in said connection flange.

9. (Cancelled)

10. (Currently Amended) The anchor of claim 8 wherein said connection portion ~~head section~~ includes first and second head ~~portions~~ sections defined by a split in said ~~head section~~ connection portion to enable said first and second head ~~portions~~ sections to be independently bent.

11. (Cancelled)

12. (Currently Amended) An anchor for connecting a building structural member to a cementitious material comprising:

a connection portion designed for connection to the building structural member above the cementitious material;

an embedment portion joined with said connection portion and designed for embedment in said cementitious material, said embedment portion including at least one anchoring leg having an upper end and a lower free end; and

first and second supporting seat members each having a supporting seat, said first and second seat members being laterally spaced from one another and joined to said embedment portion along respective first and second laterally extending and collinear bend lines ~~connection edges to said embedment portion~~.

13. (Cancelled)

14. (Currently Amended) ~~The~~ A truss anchor ~~of claim 12~~ for connecting a building structural member to a cementitious material comprising:

a connection portion designed for connection to the building structural member above the cementitious material;

an embedment portion joined with said connection portion and designed for embedment in said cementitious material, said embedment portion including at least one anchoring leg having an upper end and a lower free end; and

first and second supporting seat members each having a supporting seat, said first and second seat members being laterally spaced from one another and joined along respective first and second connection edges to said embedment portion wherein each of said supporting seats includes an outer, upwardly extending connection flange and a connection opening in said connection flange.

15. (Previously Presented) The anchor of claim 12 wherein said embedment portion includes a sloping side edge sloping upwardly and laterally outwardly from the upper end of said at least one anchoring leg.

16 -19 (Cancelled)

20. (Currently Amended) A building structure comprising:

a cementitious material;

a building structural member; and

an anchor having a connection portion connected to said building structural member, embedment portion joined with said connection portion and embedded in said cementitious material, and first and second supporting seat members each having a supporting seat for supporting said building structural member, said first and second seat members being laterally spaced from one another and joined along respective first and second laterally extending and collinear bend lines ~~connection edges~~ to said embedment portion.

21. (Previously Presented) The building structure of claim 20 wherein said cementitious material is a cementitious wall which includes a top opening to receive cementitious material and a pair of top wall edges on opposite sides of said top opening.

22. (Previously Presented) The building structure of claim 21 wherein said first and second supporting seats members are located at or above the top of said cementitious material.

23. (Previously Presented) The anchor of claim 2 wherein each of said first and second leg sections includes an inner edge in which the inner edges of said first and second leg sections are substantially collinear and wherein each of said first and second leg sections includes an outer edge in which the outer edge of said second leg section is spaced from the inner edge of said second leg section a distance greater than the distance between the outer and inner edges of said first leg section.

24. (Currently Amended) An anchor for connecting a building structural member to a cementitious material comprising:

a connection portion for connection to the building structural member;

an embedment portion joined with said connection portion for embedment in said cementitious material and including a central anchoring portion; and

first and second seat members positioned on opposite lateral sides of said anchoring portion wherein said embedment portion includes first and second side ~~edge~~ portions integrally connected with ~~sloping upwardly and laterally outwardly toward~~ said first and second supporting seat members along first and second respective bend lines.

25. (New) The anchor of claim 24 wherein said first and second bend lines are substantially collinear.

26. (New) The anchor of claim 1 wherein said first and second bend lines are substantially collinear.